

## MEKONG DELTA 4.5 AH093

### PRODUCT SPECIFICATIONS

|                         |                                                                                                  |
|-------------------------|--------------------------------------------------------------------------------------------------|
| STYLE NAME / NUMBER     | Mekong Delta 4.5 / AH093                                                                         |
| PRODUCT TYPE            | LVT                                                                                              |
| COLLECTION NAME         | Halong Bay                                                                                       |
| CONSTRUCTION            | Luxury Vinyl Tile                                                                                |
| WEAR LAYER THICKNESS    | 12 mil                                                                                           |
| INSTALLATION METHOD     | Click                                                                                            |
| GAUGE                   | 4.5 mm                                                                                           |
| FINISH                  | Enhanced Urethane Finish                                                                         |
| CLASSIFICATION          | ASTM F1700 - Class III, Type A - Smooth, Type B - Embossed                                       |
| SQUARENESS              | ASTM F 2421 - Passes - $\pm 0.10$ " max                                                          |
| SIZE AND TOLERANCE      | Tile ASTM F2055; Plank ASTM F2421 - Passes - $\pm 0.016$ "/linear foot                           |
| FLEXIBILITY             | ASTM F137 - Passes - 1" mandrel                                                                  |
| DIMENSIONAL STABILITY   | ASTM F2199 - Passes - 0.020"/linear foot max                                                     |
| RESIDUAL INDENTATION    | ASTM F1914 - Passes - Average less than 8% maximum single reading 10%                            |
| RESISTANCE TO CHEMICALS | ASTM F925 - Passes - No more than a slight change in surface dylling, surface attack or staining |
| RESISTANCE TO LIGHT     | ASTM F1515 - Passes - $\Delta E < 8$                                                             |
| RESISTANCE TO HEAT      | ASTM E649 - Class 1 ( $> 0.45$ W/cm <sup>2</sup> )                                               |
| SMOKE DENSITY           | ASTM E662 Part A - Less than 450                                                                 |
| OPTIONAL UNDERLAYMENT   | Mohawk AccuSound™ - Loose lay - Active Sound-Click                                               |
| CERTIFICATION           | FloorScore® Certified                                                                            |
| INSTALLATION            | Click                                                                                            |
| WARRANTIES              | Limited 15 Year Residential Warranty                                                             |